

Lisa 8. PERI MULTIFLEX talad ja postid

MULTIFLEX talad GT 24 laeraketises

Lae paksus [m]	0,22			0,24			0,26			0,28			0,30			0,35		
Koormus q* [kN/m²]	7,6			8,1			8,7			9,2			9,8			11,3		
Abitalade vahekaugus a [m]	0,75	0,625	0,50	0,625	0,50	0,40	0,625	0,50	0,40	0,625	0,50	0,40	0,625	0,50	0,40	0,50	0,40	
Peatalade lubatav sille Postide vahekaugus c [m]	0.60	2,99	3,18	3,42	3,09	3,33	3,59	3,02	3,25	3,50	2,95	3,17	3,42	2,88	3,11	3,35	2,96	3,19
		13,7	14,5	15,7	15,1	16,3	17,5	15,7	16,9	18,2	16,2	17,5	18,8	16,9	18,2	19,6	20,1	21,6
	0.90	2,99	3,18	3,42	3,09	3,33	3,59	3,02	3,25	3,50	2,95	3,17	3,39	2,88	3,11	3,19	2,75	2,75
		20,5	21,8	23,5	22,7	24,4	26,3	23,5	25,3	27,3	24,3	26,2	28,0	25,3	27,3	28,0	28,0	28,0
	1.20	2,99	3,06	3,06	2,87	2,87	2,87	2,69	2,69	2,69	2,54	2,54	2,54	2,39	2,39	2,39	2,06	2,06
		27,4	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0
	1.50	2,45	2,45	2,45	2,29	2,29	2,29	2,16	2,16	2,16	2,03	2,03	2,03	1,91	1,91	1,91	1,65	1,65
		28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0
	1.80	1,88	1,88	1,88	1,76	1,76	1,76	1,65	1,65	1,65	1,56	1,56	1,56	1,47	1,47	1,47	1,26	1,26
		28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0
	2.10	1,43	1,43	1,43	1,34	1,34	1,34	1,26	1,26	1,26	1,19	1,19	1,19	1,12	1,12	1,12	0,96	0,96
		28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0
	2.40	1,22	1,22	1,22	1,15	1,15	1,15	1,08	1,08	1,08	1,02	1,02	1,02	0,96	0,96	0,96	0,82	0,82
		28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0	28,0

Postid PEP 30

Posti tüübikinnitusele vastav lubatav koormus [kN]

Täis- pikkus [m]	PEP 30-150		PEP 30-250		PEP 30-300 PEP 30 G 300*		PEP 30-350 PEP 30 G 350*		PEP 30-400	
	L = 0,96 - 1,50 m Väline toru all	Sisemine toru all	L = 1,46 - 2,50 m Väline toru all	Sisemine toru all	L = 1,71 - 3,00 m Väline toru all	Sisemine toru all	L = 1,96 - 3,50 m Outer tube toru all	Sisemine toru all	L = 2,21 - 4,00 m Outer tube toru all	Sisemine toru all
1,00	35,0	35,0								
1,10	35,0	35,0								
1,20	35,0	35,0								
1,30	34,9	35,0								
1,40	34,2	35,0								
1,50	33,5	35,0	40,0	40,0						
1,60			40,0	40,0						
1,70			40,0	40,0						
1,80			40,0	40,0	40,0	40,0				
1,90			38,5	40,0	40,0	40,0				
2,00			36,8	40,0	40,0	40,0	40,0	40,0		
2,10			35,3	40,0	40,0	40,0	40,0	40,0		
2,20			34,4	40,0	40,0	40,0	40,0	40,0		
2,30			33,3	40,0	40,0	40,0	40,0	40,0	40,0	40,0
2,40			32,1	37,6	40,0	40,0	40,0	40,0	40,0	40,0
2,50			30,1	34,8	39,9	40,0	40,0	40,0	40,0	40,0
2,60					38,8	40,0	40,0	40,0	40,0	40,0
2,70					37,4	40,0	40,0	40,0	40,0	40,0

Postid PEP 20

Posti tüübikinnitusele vastav lubatav koormus [kN]

Täis- pikkus [m]	PEP 20 N 260*		PEP 20-300 PEP 20 N 300*		PEP 20-350 PEP 20 N 350*		PEP 20-400 PEP 20 G 410*		PEP 20-500	
	L = 1,51 - 2,60 m Väline toru all	Sisemine toru all	L = 1,71 - 3,00 m Väline toru all	Sisemine toru all	L = 1,96 - 3,50 m Väline toru all	Sisemine toru all	L = 2,21 - 4,00 m Outer tube toru all	Sisemine toru all	L = 2,71 - 5,00 m Outer tube toru all	Sisemine toru all
1,60	35,0	35,0								
1,70	35,0	35,0								
1,80	35,0	35,0	35,0	35,0						
1,90	35,0	35,0	35,0	35,0						
2,00	33,5	35,0	35,0	35,0	35,0	35,0				
2,10	31,9	35,0	32,2	35,0	35,0	35,0				
2,20	30,9	35,0	30,5	35,0	35,0	35,0				
2,30	29,8	35,0	29,0	35,0	35,0	35,0	35,0	35,0		
2,40	28,6	35,0	27,8	35,0	35,0	35,0	35,0	35,0		
2,50	27,1	32,9	26,9	35,0	35,0	35,0	35,0	35,0		
2,60	24,8	29,4	26,1	35,0	33,8	35,0	35,0	35,0		
2,70			24,9	31,7	32,4	35,0	35,0	35,0		
2,80			23,3	28,5	31,2	35,0	35,0	35,0	35,0	35,0
2,90			21,6	25,7	30,2	35,0	35,0	35,0	35,0	35,0
3,00			20,0	23,2	29,2	35,0	35,0	35,0	35,0	35,0
3,10					27,5	34,6	33,6	35,0	35,0	35,0
3,20					25,7	31,5	32,5	35,0	35,0	35,0
3,30					24,1	28,8	31,2	35,0	35,0	35,0
3,40					22,4	26,4	29,6	35,0	35,0	35,0
3,50					20,7	24,1	27,8	33,9	35,0	35,0
3,60							26,1	31,2	35,0	35,0
3,70							24,5	28,9	35,0	35,0
3,80							23,0	26,8	35,0	35,0
3,90							21,6	24,8	35,0	35,0
4,00							20,1	22,8	34,2	35,0
4,10									32,3	35,0
4,20									30,6	35,0
4,30									28,9	34,0
4,40									27,4	31,9
4,50									26,0	29,9
4,60									24,6	28,1
4,70									23,4	26,4
4,80									22,1	24,9
4,90									20,9	23,4
5,00									20,0	21,8

Postid MULTIPROP

Posti tüübikinnitusele vastav lubatav koormus [kN][illegible]